



Chalkboard Paint

CHK-3078

General Description

Insl-X® Chalkboard Paint is 100% acrylic and turns virtually any interior surface into a chalkboard. Create a communication space in the kitchen for the family, turn a wall in your home office into a notepad or give your kids a place in their bedroom to get creative.

- 100% acrylic resin
- For interior surfaces
- Easy-to-clean

Usage

For interior use on previously painted surfaces. Use wherever a chalkboard finish is desired. For best results, use traditional, non-liquid chalk, in lighter colors.

Colors	Black
Bases	NA

Technical Data

Vehicle	100% Acrylic
Pigment	Titanium Dioxide
Volume Solids	40 ± 2%
Spread Rate Per Quart	100 – 110 Sq. Ft.
Recommended Wet:	3.7 – 4.0 mils
Film Thickness Dry:	1.5 – 1.6 mils

Allow painted area to cure for 3 days before using. Prior to initial use, rub entire surface with a piece of white chalk and then erase using a clean, damp cloth. Because of the additives used in some varieties of chalk, which can leave a residue when erased, we recommend using lighter colored chalk designed for use on chalkboards.

Dry Time @ 77 °F	To Touch:	30 minutes
(25 °C) @ 50% RH	To Recoat:	4 hours

High humidity and cool temperatures will result in longer dry, recoat and service times.

Surface Temperature	Min:	50 °F
During Application	Max:	90 °F
Viscosity		95 ± 4 KU
Flash Point		None
Sheen / Gloss		5 – 15 @ 85°
Clean Up		Warm, soapy water
Thinner		Refer to page 2
Weight Per Gallon		10.6 lbs.
Storage Temperature	Min:	40 °F
	Max:	90 °F
VOC		< 50 g/L

Surface Preparation

Surfaces must be clean, dry and free of wax, grease, dust, mildew, water-soluble materials and scaling paint. Hard, glossy areas should be dulled with sandpaper to ensure proper adhesion.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Primer/Finish Systems

Use the appropriate Insl-X® primer if required. Follow label directions. For previously painted surfaces in good condition, apply two coats of this product. Otherwise, before and after filling in nail holes, cracks and other surface imperfections, spot prime with the appropriate Insl-X® primer. When dry, apply two finish coats of Chalkboard Paint (CHK-3078).

Application

Stir thoroughly. Apply with a quality nylon brush, short nap roller or spray gun. When brushing or rolling, apply generously using short overlapping strokes, always moving from unpainted into painted areas. Do not over apply. Let paint dry before touching up.

Do not apply in temperatures below 50 °F (10 °C).

Before Using

Allow painted area to cure for 3 days before using. Prior to initial use, rub entire surface with a piece of white chalk and then erase using a clean, damp cloth. Because of the additives used in some varieties of chalk, which can leave a residue when erased, we recommend using lighter colored chalk designed for use on chalkboards.

Compliance & Certifications

FEDERAL	✓
OTC	✓
OTC II	✓
CARB	✓
CARB07	✓
CARB19	✓
UTAH	✓
AZMC	✓
SCAQMD	✓

Limitations

- Do not apply when air and surface temperatures are below 50 °F (10 °C).

Technical Assistance

Available through your local authorized independent retailer.

call 1-866-708-9180
visit www.insl-x.com

Thinning/Clean Up

Thinning is unnecessary, but if required to obtain desired application properties, a small amount of clean water may be added. Never add other paints or solvents. Wash painting tools in warm soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.

Environmental Health & Safety Information

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



WARNING Cancer and Reproductive Harm— www.P65Warnings.ca.gov
Refer to the product label & Safety Data Sheet for product specific information.

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under “Clean Up”.

KEEP OUT OF REACH OF CHILDREN

PROTECT FROM FREEZING

**Refer to Safety Data Sheet for additional health
and safety information.**